





# HOSTAPHAN®

Hostaphan® MUVK can easily be coated or printed with functional layers. The film is optimized for high speed processing. Further details can be given on request.

## Delivery program Hostaphan® MUVK

Thickness $\mu\text{m}$	Yield		Roll length $\text{m}$	Roll-diameter $\text{mm}$	Roll length $\text{m}$	Roll-diameter $\text{mm}$
	$\text{g}/\text{m}^2$	$\text{m}^2/\text{kg}$				
15	21	48	11 200	490	33 600	830

Other roll lengths on request. Core diameter: 152.4 mm (6")

Please note that when Hostaphan® MUVK is combined with other materials or articles, the performance of the final product depends on all components and the geometry. Rigorous qualification and safety testing of the final product is always necessary, as unexpected interactions could occur.

This data sheet reflects our state of knowledge at the time this was prepared. The purpose is to provide an overview of the characteristics of our products and their potential uses. The values given reflect the typical characteristics of the film. They are not specification limits. They are neither a guarantee of specific properties nor the suitability of products in specific applications. The user must observe industrial property rights, such as patents or trademarks. The quality of our products is covered by the terms of the General Conditions of Sale of MITSUBISHI POLYESTER FILM GmbH.

Edition 01/17



 MITSUBISHI POLYESTER FILM GmbH

Kasteler Str. 45 • 65203 Wiesbaden/Deutschland • Tel.: +49 611 96203 • Fax.: +49 611 9629357